



StoreWell Side Discharge Hopper Size Guide

We are one of the few manufactures of side discharge hoppers in the UK, these are our own StoreWell range based upon Rowlands hoppers. These are polygon hoppers are of a refined high quality design which have been developed over 30 years.

All hoppers are supplied as standard with a 4" dia. blow & 6" dia. exhaust pipes, and also feed level sight glasses. Hoppers come in plain galvanized finish but for personal preference or local authority planning requirements hoppers can be sprayed in a range of landscape blending colours. The hoppers are constructed from galvanized steel sheets, with the steel support structure is from heavy gauge hot-dip galvanized steel sections. This gives our hoppers a low maintenance lifespan of 25 to 30 years when correctly cared for.

Model	Capacity			Overall Height		Diameter	
	Tonnage	Cu. Metres	Cu. Feet	Metres	Feet	Metres	Feet
S479SD	8.7	13.5	479	5.94	19' 6"	2.64	8' 8"
S594SD	10.9	16.8	594	6.54	21' 6"	2.64	8' 8"
S710SD	13	20.1	710	7.14	23' 5"	2.64	8' 8"
S825SD	15.2	23.4	825	7.75	25' 5"	2.64	8' 8"
S941SD	17.3	26.6	941	8.35	27' 5"	2.64	8' 8"
S983SD	18	27.8	983	7.79	25' 7"	3.01	9' 10"
S1134SD	20.9	32.1	1134	8.39	27' 7"	3.01	9' 10"
S1285SD	23.7	36.4	1285	8.89	29' 6"	3.01	9' 10"

Notes: Tonnage capacities based on pellets at 650 kg / m³

Overall heights are based on outlet at 1m (3') above ground, high level outlet will increase height.

Extras:

- ✔ Moist air roof vent (standard on dairy hoppers)
- ✔ Side & roof ladders
- ✔ Bag-off chute
- ✔ Additional sight glasses
- ✔ Outlet adaptors
- ✔ Side access / inspection door
- ✔ Other custom parts & equipment



All hoppers in our range can be recycled.

Also available Storewell centre discharge hoppers Crowley centre discharge hoppers, Chore-Time augers, milking parlours, large range of spares and hopper relocation service.

For further details please see our product guide, website or contact us.

